

PRO-Line Positioners

Welding Positioner PRO 08

Features

- The turntable PRO 08 has a precise drive unit with faceplate that is mounted on a stable floor stand.
- Workpieces can be positioned over a pivoting range of 0° - 90°.
- The rotary motion occurs via a direct current gearmotor with worm gear and is infinitely adjustable.
- Table diameter: 300 mm. The surface is chrome-plated as a protection against weld spatters.
- The control panel is easy to understand and operate.
- Start/stop via location-independent foot switch.
- Adjustment of turning speed and rotating direction directly via the machine.
- HF-protected.

Scope of delivery:

- 1 Control (integrated)
- 1 Foot switch

THE HOUSING OF THE TURNTABLE MUST BE CONNECTED DIRECTLY TO THE HOUSE GROUND!



Model	PRO 08
Supply voltage	AC 230 V/50 Hz
Ground connection	300 A/100 %
Tilting range	0° - 90°
Table diameter	300 mm
Hollow shaft	no
Mounting hole circle Ø	100mm up to max. 264 mm
Schlitzbreite Drehteller	14 mm
Speed	0,7 - 7 rpm
Rotating directions	cw/ccw
Max. load A	80 kg
Measurements (L x W x H) mm	450 x 330 x 360
Weight	36 kg
Item no.	02.30.01.10010

Note

suitable for Three-jaw Chuck 160D and Chuck 200D.



PRO-Line Positioners

Welding Positioner PRO 08

