


ETX-Easy-Tool-Exchange



With integrated water dosing



DIF-Diamond Floating Device

DSM 450 – Universal use

Compact in design and easy to use. The DSM 450 is an allpurpose machine for stripping, scarifying, grinding and polishing. For transport purpose it can be dismantled in two parts. Very comfortable to operate as it comes standard with anti-shock drive mechanism and water control direct from the handle when grinding wet.

Applications

Cleaning of formwork, removal of coatings, renovation and polishing of concrete and stone floors, cleaning of scaffolding.

Features

- Dismountable for transport
- ETX-Easy Tool Exchange
- DIF-Diamond Floating Device
- Speed control R/L
- Standard with a water dosing device
- Water tank

DSM 450



Concrete polishing



Tools for any application



Robust in design

DSM 530 – Low in vibration with integrated water dosing

A conventional grinder for concrete, screed and natural stone floors. Very comfortable to operate as it comes standard with anti-shock drive mechanism and water control direct from the handle when grinding wet.

Applications

For subfloor preparation and floor polishing.

Features

- Ergonomical in operation
- Standard with integrated water dosing for wet grinding
- Dismountable for transport
- DIF-Diamond Floating Device = less vibration
- Speed control R/L
- Power indicator
- Water tank

DSM 530



Technical data		DSM 450	DSM 450	DSM 530
Voltage	V	400	203	400
Frequency	Hz	50	50	50
Power output	kW	2,2	2,2	4,0
∅ – working width	mm	450	450	530
∅ – grinding disc	mm	3x180	3 x 180	3 x 200
Grinding pressure	kg	88	88	114
Weight	kg	118	125	162
Working to the edge	mm	10	10	10
Tool speed	r.p.m.	400-1200	400-1200	400-1200
Tank	l	10	10	10
∅ – suction outlet	mm	50	50	50
Ref. No.		719001	719000	715500