



For Earth, For Life
Kubota

GR

KUBOTA DIESEL RIDE-ON MOWER
GR2120/GR2120S

A sleek and stylish ride-on mower loaded with professional features, the GR2120/GR2120S gives you first class results every time.

Introducing a revolutionary technology

**GLIDE
STEER**



Easy to use, comfortable to operate and a pleasure to look at, the Kubota GR2120 is unrivalled for professional results.

Results, results, results. If that's what you're looking for there's no better choice than the GR2120. This high-end ride-on boasts our unique Glide Steer, an innovative Direct Chute System, a 21-horsepower engine, and a newly designed grass collector. Test drive the GR2120 today and experience unmatched performance in both efficiency and final finish.

Introducing a revolutionary technology

GLIDE STEER



Performance

The brain and brawn to tackle the toughest tasks.

Glide Steer

This revolutionary technology enables the GR2120 to turn so sharply, it leaves only a 100 cm circle of uncut grass. Our unique Glide Steer feature makes cutting around trees, poles, and other narrow objects extremely efficient. Plus, because the inner rear wheel spins freely when turning, the grass is not damaged.

1 When driving in a straight direction, the GR2120 provides outstanding traction with its All-wheel drive, even on slopes.

2 For the sharpest turn possible, both the front wheels turn an incredible 70° at which point the inside rear wheel spins freely.

3 By spinning freely, the inside wheel does not damage the grass. Once the front wheels are straight, it resumes All-wheel drive.

Powerful Kubota engine

Tapping Kubota's legendary heritage of formidable engine designs, the GR2120 is equipped with a 21-horsepower, 3-cylinder diesel power plant. It generates a high torque rise that easily handles hours of heavy-duty mowing, even in long, wet grass, with a grass collector mounted.



Ultra-durable shaft drive

Unlike the belt-drive system utilised in gasoline mowers, our shaft-drive transmission, shaft-drive PTO, and hydraulic PTO clutch are incredibly durable and worry-free.



Fatigue-reducing power steering

Feather-touch power steering enhances manoeuvrability, reduces fatigue, and makes operating the GR2120 possible for virtually anyone.



Versatile HST transmission

Kubota's reputable and versatile HST transmission is easily controlled by a single foot pedal and produces a maximum travel speed of 10km/h.



Suspension seat/full-flat deck

Oversized and generously padded, the GR2120's parallel linkage suspension seat can be adjusted to provide a high level of comfort to a wide range of operators. Its full-flat deck minimises operator fatigue by offering plenty of legroom.



Maintenance

The sophisticated grass collector design makes catching and dumping grass easy.

The grass collector on the GR2120 maintains a large capacity, yet, is lighter, easier to empty and utilises innovative mower technologies to prevent clogging.

Large capacity grass collector

The 450-litre grass collector has been made lower and longer to minimise clogging and reduce time between dumping. The collector also boasts lighter materials for easier handling.



Collector lever and lid

A gas-spring assist mechanism on the collector lever used for dumping makes lifting, even a full basket, easy. The lid of the collector opens wide, making maintenance easy work.



Well-designed duct

A handy electronic sensor is added to signal when the collector needs to be emptied. The wide duct leading from the mower deck is designed to move grass smoothly. A lever on the side of the tractor allows the operator to expel excess grass from the duct without leaving the tractor seat.



Turf

Our Direct Chute System ensures professional results.

The GR2120's Direct Chute System efficiently cuts and channels grass straight back into an integrated rear grass collector. The deck's cutting width is an ample 48 inches, and thanks to its centre-discharge configuration, you can execute tight, tree-hugging turns in either direction. For those who prefer a side-discharge mower, the GR2120S's mower deck is constructed of durable 10-gauge steel and is designed with a 5-inch deep shell. Whichever system you choose, you'll be assured professional and lasting results.



Side-discharge Mower

Note: The above photo is shown with respect to French regulation.



Easy reach cutting height adjustment dial



Deck cleaning pipe for connecting water hose



Hydraulic mower lift lever



Ultra-durable, long-life hexagonal belt



Rear Deflector

An optional rear deflector is available for times when you choose not to use the grass collector. This deflector discharges grass and dust directly onto the ground and easily attaches to the end of the duct, which leads from the mower deck.

Note: Some of the features shown may differ from those of the actual model.

Specifications

Model		GR2120	GR2120S
Engine			
Model		Kubota D782-E3-GX	
Type		3 cylinder, diesel, water-cooled	
Total displacement	cc	778	
Gross horsepower	HP (kW)	21,0 (15,6)	
Engine layout		Horizontal	
Fuel tank capacity	ℓ	18	
Dimension			
Overall length	mm	2880	2000
Overall width	mm	1280	1550
Overall height	mm	1205	
Wheelbase	mm	1280	
Tread			
Front/Rear	mm	825/820	
Weight (w/mower and grass collector)	kg	515	445
Tyre size			
Front/Rear		16×7,5–8/23×10,50–12	
Transmission			
Hydrostatic transmission			
Transmission drive			
Shaft drive			
Speed control			
Single foot pedal			
Front-wheel drive			
Glide Steer			
Travelling speed			
Forward/Reverse	km/h	0–10,0/0–5,0	
Brake			
Internal expanding brake			
PTO clutch			
Hydraulic wet multi discs			
Mower deck drive			
U-joint shaft			
Steering system			
Glide Steer, fully hydraulic power steering			
Operator's deck			
Flat			
Seat adjustment			
Slide			
Seat suspension			
Parallel linkage			
Fuel gauge			
Std.			
Hour meter			
Std.			
Easy checker			
Std.			
Mower OPC.			
Std.			
Travel OPC.			
Std.			
Blade shut off brake			
Built-in clutch			
Mower shut off when collector open		Std.	-
Grass collector			
Capacity	ℓ	450	-
Dumping system		Manual	-
Material of bag		Fabric / Steel	-
Optional accessories & implements		Cruise control, rear deflector	Cruise control, mulching kit

Mower Specifications

Cutting width	in. (cm)	22 (48)	
Mower system		Direct chute	Side discharge
Mower blade drive		V. / hexagonal belt	V.
Lifting device		Hydraulic	
Mower mounting method		Quick attach	
Cutting height	mm	25–102	
Cutting height adjustment		Dial	
Cutting height position		11	
Number of blades		3	
Direction of rotation		2 clockwise viewed from operator, 1 counter clockwise	1 counter clockwise
Minimum uncut diameter	m	1,0	
Mower deck ground clearance	mm	135	140

The company reserves the right to change the above specifications without notice.

©2013 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 214500 Fax (01844) 216685
E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>