



Paving Block Extractor SZ with Locking Device

An essential tool for any contractor who lays paving blocks or carries out repairs to paved surfaces. Adjustable to fit any size and shape of paver.

With Locking Device!

The operator does not need to continually squeeze the SZ-handles together!

The spring steel blades can be driven into the joints of existing pavements without problems by the combination hammer KH.

▷ The gripping width can be adjusted without tools.

▷ Easily exchangeable, high quality profiled spring steel blades.

Paver Lifter SAH

To lift out uncompacted pavers quick and easy,

for example when marker pavers in different colour should be laid in.

Type	Surface protection	Gripping Range W mm (in)	Dead Weight kg (lbs)	Order-Number
SZ [Ⓞ]	galvanized	90 – 330 (3 1/2 – 13")	4 (9)	5180.0030
SAH [Ⓞ]	galvanized	90 – 400 (3 1/2 – 15 3/4")	4,9 (11)	5180.0050
SZ-Set consisting of Paving Block Extractor, Extraction Foot Lever, Combination Hammer				5180.0048

See page 4.6 for a special device for removing slabs – the PZ.

Accessories:

Extraction foot lever AHW for quick loosening of pavers – including 2 spare blades + wire brush.

(When pavers are extremely interlocked the vibration of a hammer drill can be used).

Type	Dead Weight kg (lbs)	Order-Number
Extraction Foot Lever AHW [Ⓞ]	1,5 (3,3)	4180.0036
Combination Hammer KH (with a hard steel side and a "soft" Nylon side)	0,8 (2)	4180.0037
Spare blade for SZ short per piece		4180.0001
Spare blade for SZ long per piece		4180.0003



Alignment Bar RE

For aligning the paving stones before they are permanently set.

joints using a hammer.

▷ With two handles, a foot bar and a hammering surface to drive it into the paver

▷ With exchangeable, robust, sharp-edged hardened spring steel blade for driving into the hinge joints.

▷ Durable galvanized surfaces.

Type	Dead Weight kg (lbs)	Order-Number
RE [Ⓞ]	1.5 (3.3)	5180.0011
Spare blade for RE/MRE	per piece	4180.0002



Multiple Alignment Bar MRE

The „Turbo Accelerator“ for alignment work: Instead of moving only one row of pavers, the MRE can move 4 or up to 5 rows at the same time. Alignment work is done 4 - 5 times quicker!

▷ Especially suitable for alignment work on mainly rectangular shaped pavers

▷ With 4 exchangeable, adjustable, sturdy, sharp edged hardened spring steel blades.

▷ With 2 handles and one hammering surface to drive it into the paver joints by hammer.

▷ Durable galvanized surfaces.

Type	approx. Working Width mm (in)	Dead Weight kg (lbs)	Order-Number
MRE [Ⓞ]	650 (25 1/2")	5 (10)	5180.0045

Adapter or special designs for dentated pavers (e.g. Uni pavers) on request.

Rubber Hammer GH

For aligning the paving stones before they are permanently set.

▷ With easily exchangeable, highly wear resistant replaceable rubber caps.

Light-weight, available with long or short handle for work in optimal position.

▷ The hammer remains vertical after use because of the rectangular shape of the rubber caps.

Type	Length of handle mm (in)	Dead weight kg (lbs)	Best.-Nr.
GH	800 (31 1/2")	2,2 (5)	5180.0012
GH-K	400 (15 3/4")	1,8 (4)	5180.0051
Rubber cover for GH/GH-K		per piece	4180.0006

Paver Set

Consisting of Paving Block Extractor, Alignment Bar and Rubber Hammer GH **5180.0014**

[Ⓞ] Durable surface protection by galvanizing



011016 Technical data contained in this catalogue can be modified without prior notice in the interest of progress. No liability accepted for any misprints, mistakes and errors.