The all-rounder



TRANSMOBIL TM Installation Carrier – Transporting and laying kerb stones

A compact universal machine – transport and handling of palletized building material and vacuum installation all in one. The powerful vacuum laying unit allows the immediate installation of heavy construction elements – effortless and without physical strain.

Chassis with rubber chains for uneven terrain, combined with a vacuum hose lifter for installation work up to 200 kg lifting force. (250 kg at reduced outreach)

- Hydraulic mast angling in seconds, boom can be swung easily and the installation material positioned exactly
- Highest Safety Standards: The SAFESTOP ensures that the knuckle boom jib cannot swing into the traffic area

Туре	Power	Reach mm (in)	Carrying Capacity of Vacuum Laying Unit* kg (Ibs)	Payload kg (Ibs)	Dead Weight kg (Ibs)	Order- Number
TM-150-B-XL	petrol engine 8,2 kW Honda GX390	3,000 (118")	150 (330)	1,500 (3,300)	approx. 1,300 (2,850)	5222.0010
TM-150-D-XL	diesel engine 9,6 kW Hatz Silent Pack	3,000 (118")	150 (330)	1,500 (3,300)	approx. 1,540 (3,400)	5222.0011
TM-150-D-A-XL	diesel engine 9,6 kW Hatz Silent Pack	3,000 (118")	150 (330)	1,500 (3,300)	approx. 1,540 (3,400)	5222.0012
TM-150-WD- A-SILENT-XL	diesel engine 10,8 kW Kubota	3,000 (118")	150 (330)	1,500 (3,300)	approx. 1,540 (3,400)	5222.0013
TM-GGP	Essential add-on once the lifting capacity exceeds 150 kg. Installation material, such as kerb stones serve as counterweight.			250 (552)	10 (22)	4222.0070

The following two models are equipped with electronic, fully automatic boom alignment – makes work even quicker and particularly user-friendly. Positioning of laying elements without physical effort:

- TM-150-D-A-XL: with sound insulated Hatz Silent Pack diesel engine
- TM-150-WD-A-SILENT-XL: extremly silenced version with water-cooled Kubota diesel engine, noise emission < 80 dB

Without fully automatic boom alignment:

TM-150-B-XL:

diesel engine

with Honda petrol engine

TM-150-D-XL: with sound insulated Hatz Silent Pack



* With more poweful lifting hose unit, proper suction plate etc. and platform for counterweight TM-GGP upgradeable to 200 kg lifting capacity when fully extended and up to 250 kg at reduced outreach of 500 mm.

More than 1.000 different suction plates are available, see page 32 for examples.

5